

Ingersoll Rand®

Rotary Screw Air Compressors

SSR®45- 75kW / 75-100HP



 **Ingersoll Rand®**

SSR 45-75 kW / 75-100HP

Looking for a rugged, reliable and energy efficient air compressor? The Ingersoll-Rand SSR is for you. With our integral gear drive system, 8000-hour coolant, and leak-free design you can count on the SSR for years to come.

If your business demands any of these then check out the SSR:

- Reliability
- Ease of installation
- Accurate information
- Easy and low cost of maintenance
- Efficiency
- Quiet operation
- Flexible options



There's more to the picture

Providing air solutions is our specialty. We offer compressed air audits, system design assistance, and other services and products that maximize the efficiency of your entire plant air system.

LINK 1 – Air Compressor:

An air compressor is the first link in a chain that acts as a dependable supply of air to your plant. Shouldn't the strength of the other links matter?

LINK 2 – System components:

We offer a complete lineup of compressed air dryers, filters, Simclair distribution pipework and other accessories that work seamlessly with your SSR rotary compressor to provide the air quantity and quality you need.

LINK 3 – Service

Ingersoll-Rand is known the worldover for its extensive and highly reliable service organization. Factory certification to service SSRs is a rigorous process unmatched in the industry. Our

worldwide distribution network knows what to do and how to do it.



LINK 4 – Manufacturer:

Ingersoll-Rand is the compressed air solutions global leader with well over 100 years of experience in the manufacture of compressed air products. We've earned our market-leading position through our commitment to the highest levels of customer service and product performance, reliability and quality.




Package design

- It's tough, quiet, and easy to service

Higher Ambient Rating – Can you afford a shutdown in the heat of summer? The SSR operates easily in ambient temperatures up to 115°F/46°C. Even if you're not in a sweltering climate, it ensures fewer nuisance shutdowns due to summer heat or dirty coolers.

Easy Installation – Set it down, hook it up to the proper electrical service and piping system, cover the forklift holes and let it go. No vibration mounts are required.

Quiet operation – A subassembly isolates the drive train from the package for virtually vibration free and quiet operation.



Superb Serviceability – Routine maintenance is done through one convenient latched panel on the front of the machine making machine servicing easier and quicker.

Tested as a Complete Package – Every SSR completes our state of the art computer based performance and operations test. This multi-point test ensures our rigid manufacturing quality standards have been met as well as trouble-free operation of the unit, beginning with the initial start-up at your facility.



The SSR Drive Train

There are many reasons that customers like you consistently give us high ratings for quality and reliability. The SSR drive train is certainly one of them. First used in the 1970s, the SSR drive train has proven itself over 100,000 times.


Superior Airend Design – At the heart of the SSR is our time-proven rotary screw airend, known for trouble free operation with minimal maintenance. All airends are designed and built in-house, guaranteeing critical quality control. The airends are built on technically advanced machinery that is generations ahead of what other manufacturers use. This ability to hold tolerances measured in microns increases the reliability and life of the airend. The airend is a robust design, built with premium materials.

Integral Gear Drive – It's the only drive system that is maintenance free and totally isolated from the environment.

The Dedicated Motor – Compressor motors are usually one of the hardest running motors in a plant. If your business depends on compressed air, then it depends on the quality and strength of the motor. The extra toughness designed and built into the SSR motor means it will run when other motors quit. Maintenance and repair on the SSR motor is just like any other motor you own.

Intellisys® – Total control at your fingertips.


The SSR comes standard with the Intellisys controller—the most advanced active microprocessor available on any compressor. First built into SSRs in the late 1980s, Intellisys has been updated to employ the latest technology, increasing the reliability while keeping it simple.



- Roller bearings for line contact rather than point contact
- Duplex arrangement for reliability


The Coolant Dam - An IR innovation insures clean oil under any and all conditions especially during start-up

All bearings are vacuum degassed for harder, truer bearing surfaces



Advanced rotor profile for efficient design

Six (6) Display Standards



Seventeen (17) fault warning and/or shutdowns


Nine (9) adjustable operating parameters

Simple use – You don't need to be a computer guru or symbol reader to use the Intellisys controller. Information is displayed in clear, plain text and not in codes. Adjustments are easily made through the finger touch control panel and there are no pressure switches to drift or adjust.

More information, more accurate – Intellisys constantly monitors and displays exactly what's happening in your SSR and displays it on the face panel. That same information can be sent via modem to your service provider for trending or it can be sent in a modbus protocol to your building control system.

Time saving diagnostics – The Intellisys monitors 11 key internal functions of the SSR. If any of those deviate from its preprogrammed limit, the controller will automatically warn and, if required, shutdown the compressor. The display then indicates the problem and the sequence of events leading to the shutdown. This feature reduces costly troubleshooting and minimizes downtime. Since Intellisys remembers what all operating parameters were prior to shutdown, the restarting process is a snap.

The Integral Gear Drive-Maintenance free and totally isolated from the ambient. It's an ideal way for a transmission system to run.




AGMA 11 gears with permanent alignment

Oversized motor bearings and all copper windings


Class F insulation with a Class B Rise

Ultracoolant – You'll be surprised by the advantages of using UltraCoolant. First, UltraCoolant has a 2-year/8000 hour life. The coolant is changed less often, keeping maintenance costs to a minimum. Secondly, since UltraCoolant was designed specifically for rotary compressors, it assures uninterrupted service by lubricating, sealing, and cooling under all normal operating conditions. Third, UltraCoolant's superior separating properties combined with our patented separator system means less coolant is passed downstream to your plant's processes. Lower coolant carryover equals less cost for coolant make-up. Finally, UltraCoolant's lack of hydrocarbons eliminates the chance of varnish formation. Varnish shortens separator life, coats rotors, bearings and heat exchangers (raising operating temperatures) and reduces airend reliability.

Patented Separator Design – Our patented two stage conical baffle separator minimizes coolant carryover to your plant and reduces the amount of make-up replaced. This design also reduces the impact that overfilling or underfilling can have on coolant carryover.




Inherent Leak Free Design – By reducing the number of fittings and using SAE O-ring fittings on all connections larger than 1/4" (6 mm), we've significantly reduced the potential leakage problem associated with conventional threaded connections and piping schemes.



Options and Accessories

Upper range modulation with Automatic Control Selector – For those plants where the demand profile is high or storage is minimal, upper range modulation stabilizes plant air pressure, reducing cycling of components with a minimal power penalty. Automatic Control Selector uses the Intellisys' built in intelligence to monitor air consumption and choose the appropriate control mode.



Remote start/stop – This option gives you offsite on/off control.

Star Delta Starting – A motor requires 600% of its full load amps to start. With star delta starting, the current used to start is only 200%, resulting in a cushioned start for both mechanical and electrical components (standard on 50Hz units).

Outdoor modification – Outdoor modification includes IP65 option and moves the package discharge from the top of the package to the side.

Heavy Duty filter – The heavy duty air filter is designed for applications where the heavy dust load would cause the air filter to plug early.

Alternate coolants – H1F food grade or diester-based SSR coolant are available.

Condensate Separator System (CSS) – Provides clean water disposal with minimal operating costs.

Intellisys System Controller (ISC) – Maintains system pressure while minimizing operating costs.

IP65 – For those applications where the compressor will be exposed to water.

Watercooled – SSRs can be outfitted with a variety of watercooled heat exchangers. The standard cooler is admiralty brass with options existing for 90/10 copper nickel, 70/30 copper nickel and stainless steel.

50Hz SSR 45-75kW Performance

Free Air Delivery - M³/min(1)

Nominal kW	ML 7.5 barg	MM 8.5 barg	MH 10 barg	MJ 11.4 barg	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
45	7.4	7.1	6.5	-	1689	1605	1696	953
55	10.1	9.1	8.3	7.6	1689	1605	1696	1270
75	13.0	12.1	11.0	10.2	1689	1605	1696	1315

60Hz SSR 75-100HP Performance

Free Air Delivery - CFM (1)

Nominal HP	XF 100 psig	EP 125 psig	HP 140 psig	XP 165 psig	Length (in)	Width (in)	Height (in)	Weight (lbs)
75	386	332	299	248	67	63	67	2800
100	495	446	412	358	67	63	67	2900

(1) FAD (Free Air Delivery) CFM and M3/Min. are ratings of full package performance in accordance with CAGI-PNEUROP acceptance test standard PN2CPTC2 or ISO1217: 1996 Annex C.

More Than Air. Answers.

Online answers: <http://www.air.ingersoll-rand.com>



Ingersoll-Rand air compressors are not designed, intended or approved for breathing air. Compressed air should not be used for breathing air applications unless treated in accordance with all applicable codes and regulations.

Nothing contained in this brochure is intended to extend any warranty or representation, expressed or implied, regarding the products described herein. Any such warranties or other terms and conditions of sale shall be in accordance with Ingersoll-Rand's standard terms and conditions of sale for such products which are available upon request.

Product improvement is a continuing goal at Ingersoll-Rand. Designs and specifications are subject to change without notice or obligation.

Tel. +66(81)689-1726 Fax. +66(2)944-5686
E-mail. sale@airvac-thai.com
Website: www.airvac-thai.com.com